

7G14A



■ Features

- Compact size using flat wire
- Low radiation noise by magnetically shielded construction
- Small size, low resistance and High current

Magnetic structure :




Weight : 8.9 g

■ Applications

- Audio Visual/Mini System, AV Amplifier, for Professionals
- Automotive/Car Audio
- Others/Power Supply

■ Dimensions



(Unit : mm)



SAGAMI ELEC CO., LTD.
<https://www.sagami-elec.co.jp>

10-30, Ichibashimo-cho, Tsurumi-ku, Yokohama, Kanagawa 230-0024, Japan
Over Seas Sales Dept. TEL : +81 45 511 3141, E-mail : ossg@sagami-elec.co.jp
Engineering Dept. TEL : +81 45 521 4543

 The contents of this catalogue are subject to change without notice.

■ Specifications

SAGAMI Part No.	Inductance (μ H)	DCR (m Ω)		DC Saturation Allowable Current (A)	Temperature Rise Allowable Current (A)
		max.	Typical		
7G14A-100M	10 $\pm$ 20%	5.90	4.90	8.30	7.80
7G14A-150M	15 $\pm$ 20%	8.30	6.90	7.50	7.30
7G14A-220M	22 $\pm$ 20%	10.0	8.30	7.00	6.60
7G14A-270M	27 $\pm$ 20%	15.7	13.2	6.50	5.40
7G14A-330M	33 $\pm$ 20%	17.5	14.1	6.10	5.10

Inductance Measuring Condition:1kHz,1V

DC saturation allowable current:The current value which inductance decrease within 25% from the initial value

Temperature rise allowable current:The rise in temperature of core surface is within 40℃



SAGAMI ELEC CO., LTD.
<https://www.sagami-elec.co.jp>

10-30, Ichibashimo-cho, Tsurumi-ku, Yokohama, Kanagawa 230-0024, Japan
 Over Seas Sales Dept. TEL : +81 45 511 3141, E-mail : ossg@sagami-elec.co.jp
 Engineering Dept. TEL : +81 45 521 4543

The contents of this catalogue are subject to change without notice.